

Wt - Bug #3212

setAppRoot(): too late

05/26/2014 06:22 PM - Saif Rehman

| | | | |
|--|-----------|------------------------|------------|
| Status: | Feedback | Start date: | 05/26/2014 |
| Priority: | Low | Due date: | |
| Assignee: | Wim Dumon | % Done: | 0% |
| Category: | | Estimated time: | 0.00 hour |
| Target version: | | | |
| Description | | | |
| I start my application with ---approot "..." command. And when I call WServer::setServerConfiguration(argc, argv, WTHHTTP_CONFIGURATION) to set up the WServer an error is shown "setAppRoot(): too late, already configured". | | | |
| It's not fatal however it is a false error message since I never set approot before that. | | | |

History

#1 - 06/02/2014 01:46 PM - Wim Dumon

- Status changed from New to Feedback

Hi,

I can't seem to reproduce this. I start the hello world example with ---approot but I don't see that error. Can you put a breakpoint on that setAppRoot method and check from where it's called?

BR,

Wim.

#2 - 06/11/2014 04:48 PM - Koen Deforche

- Assignee set to Wim Dumon

#3 - 06/19/2014 02:35 PM - Saif Rehman

My main.cpp

```
WServer Server = WServer(argv[0], "wt_config.xml");
try
{
    Server.Initialize();
    Server.setServerConfiguration(argc, argv, WTHHTTP_CONFIGURATION); <---- HERE
    ...
}
```

in WServer.C, function void WServer::setServerConfiguration()

```
if (!appRoot.empty())
    setAppRoot(appRoot); <--- HERE
```