

Wt - Bug #795

Connect a button to TinyMce push button

04/19/2011 07:14 PM - Francesco Alfano

Status:	Closed	Start date:	04/19/2011
Priority:	Urgent	Due date:	
Assignee:	Koen Deforche	% Done:	0%
Category:		Estimated time:	0.00 hour
Target version:	3.3.4		

Description

Hello,

How to connect a button from tinyMce editor (like save, or newdocument as shown in <http://tinymce.moxiecode.com/tryit/full.php>) to a "Wt connect" to handle the push button event ?

How to pass parameter to tinyMCE.init like

```
tinyMCE.init({force_p_newlines' : false, 'forced_root_block' : 'div' }) ?
```

Thanks in advance for your help, Francesco.

History

#1 - 04/19/2011 07:19 PM - Francesco Alfano

I'm sorry it is support request, not a bug !!!

#2 - 04/26/2011 10:33 AM - Koen Deforche

- Status changed from New to Feedback

Hey Fransesco,

Could you try the following method:

<http://redmine.webtoolkit.eu/boards/1/topics/1071>

Regards,

koen

#3 - 04/26/2011 07:17 PM - Francesco Alfano

Koen Deforche wrote:

Hey Fransesco,

Could you try the following method:

<http://redmine.webtoolkit.eu/boards/1/topics/1071>

Regards,

koen

Thanks for your response,

I can't use the method that you have proposed because the save button is already present in toolbar !

i've used the following code which automatically add a save button in toolbar

\"

```
teTextEditor = new Wt::WTextEdit(teContainer);
```

```
teTextEditor->setExtraPlugins("autolink,lists,spellchecker,pagebreak,style,layer,table,save,advhr,advimage,advlink,emotions,iespell,inlinepopups,inse
```

```
rdatetime,preview,media,searchreplace,print,contextmenu,paste,directionality,fullscreen,noneditable,visualchars,nonbreaking,xhtmlxtras,template");
teTextEditor->resize(700, 400);

teTextEditor->setToolBar(0,
"save,newdocument,|,bold,italic,underline,strikethrough,|,justifyleft,justifycenter,justifyright,justifyfull,|,styleselect,formatselect,fontselect,fontsizeselect"
);
\"
```

#4 - 05/05/2011 11:10 PM - Koen Deforche

Hey Fransesco,

I see. So you actually want to react to an event of an existing standard button? Have you found whether this is possible in the documentation of TinyMCE? If so, I can help you with how to integrate it in your Wt application.

Regards,

koen

#5 - 05/06/2011 09:04 AM - Francesco Alfano

Koen Deforche wrote:

Hey Fransesco,

I see. So you actually want to react to an event of an existing standard button?

Yes !

Have you found whether this is possible in the documentation of TinyMCE? If so, I can help you with how to integrate it in your Wt application.

Regards,

koen

Hello,

I have already contacted, you can see my post at:

<http://tinymce.moxiecode.com/forum/viewtopic.php?id=25669>

Thanks, for your time.

#6 - 03/09/2015 11:14 PM - Koen Deforche

- Status changed from Feedback to Resolved
- Assignee set to Koen Deforche
- Target version set to 3.3.4

We added a rendered() accessor that allows you to do this:

```
edit->rendered().connect(std::bind( [=] () {
    edit->doJavaScript(edit->jsRef() + ".ed.onSaveContent.add("
        "function() { "
        ""alert('Dovrei salvare i dati su server'); } );");
}));
```

#7 - 03/17/2015 08:25 AM - Koen Deforche

- Status changed from Resolved to Closed