

Wt - Bug #7957

Regression in Wt 4.5.0: behind-reverse-proxy doesn't work right with dedicated process mode anymore

01/05/2021 05:51 PM - Roel Standaert

Status:	Closed	Start date:	01/05/2021
Priority:	Normal	Due date:	
Assignee:	Roel Standaert	% Done:	100%
Category:		Estimated time:	0.00 hour
Target version:	4.5.1		

Description

The child processes will disable behind reverse proxy and set 127.0.0.1 and ::1 as trusted proxies.

However, the parent process merely adds extra proxies to the X-Forwarded-For header. Any trusted proxies herein should still be considered trusted proxies by the child process.

The fix is to leave the behind reverse proxy option alone (the old behavior), and add 127.0.0.1 and ::1 to the existing list of reverse proxies.

History

#1 - 01/05/2021 05:51 PM - Roel Standaert

- Target version set to 4.5.1

#2 - 01/06/2021 04:04 PM - Roel Standaert

- Status changed from InProgress to Implemented @Emweb

#3 - 01/14/2021 09:50 AM - Roel Standaert

- Status changed from Implemented @Emweb to Resolved

#4 - 08/05/2021 03:40 PM - Roel Standaert

- % Done changed from 0 to 100

#5 - 10/19/2021 11:01 AM - Roel Standaert

- Status changed from Resolved to Closed