

JWT - Bug #8765

JWT 4.5.0 trustedProxies is null when initializing Configuration from a XML

07/04/2021 02:02 AM - Daniel Jeronymo

Status:	Closed	Start date:	07/04/2021
Priority:	Immediate	Due date:	
Assignee:	Roel Standaert	% Done:	100%
Category:		Estimated time:	0.00 hour
Target version:	4.5.1		
Description			
<p>When initializing Configuration with a XML file this will call the XML constructor and the "trustedProxies" variable isn't initialized, eventually this will throw an exception at Configuration:966 "for (Network trustedProxy : trustedProxies)". This is a version breaking bug for whoever uses configuration files.</p> <p>Fix is simple, change Configuration:185 to initialize the variable: "private List trustedProxies = Collections.emptyList();".</p> <p>This variable initialization can then be removed from Configuration default constructor.</p>			

History

#1 - 07/05/2021 01:43 PM - Roel Standaert

- Status changed from *New* to *InProgress*
- Assignee set to *Roel Standaert*

#2 - 07/05/2021 01:43 PM - Roel Standaert

- Status changed from *InProgress* to *Review*

#3 - 07/19/2021 05:02 PM - Roel Standaert

- Status changed from *Review* to *Implemented @Emweb*

#4 - 10/07/2021 04:44 PM - Roel Standaert

- Status changed from *Implemented @Emweb* to *Resolved*
- Target version set to *4.5.1*
- % Done changed from *0* to *100*

#5 - 02/15/2022 10:15 AM - Roel Standaert

- Status changed from *Resolved* to *Closed*